

Front bucket seats

Front bucket seats KIT CONTENTS:

Seat Cover Driver
Seat Cover Passenger
Headrest Cover



Slide the cover over the seat



Align the headrest opening and
connect velcro





Place webb strap between seat
top and bottom



Pull webbing between seat and pull
webbing strap



Connect webbing strap with ladderlock





Place cover over the bottom seat



Attach pillow to the side of the seat frame



Pass webbing under seat reach for webbing to connect with buckle



Stay clear of any electrical connectors under the seat

Carhartt Front Seat Covers

IR 23JA18

PART NO.

84138071

SHEET

3

OF

15

ALL INFORMATION WITHIN ABOVE BORDER TO BE PRINTED EXACTLY AS SHOWN ON 8.5 x 11 WHITE 16 POUND NON-BOND RECYCLABLE PAPER. PRINT ON BOTH SIDES, EXCLUDING TEMPLATES. TO BE UNITIZED IN ACCORDANCE WITH GM SPECIFICATIONS.

DATE	REVISION	AUTH	DR
23JA18	Initial Release - Gino LeDonne	2596136	

TITLE	INSTALLATION INSTRUCTIONS		
	Carhartt Front Seat Covers		
PART NO.	84138071	SHEET	3 OF 15



Connect velcro to secure outside flap

 Keep the flap routed behind the seat belt attachment

Headrest



Slide cover on headrest

Headrest



Connect velcro

Sièges baquets avant

Sièges baquets avant
CONTENU DE LA TROUSSE :

- Housse de siège conducteur
- Housse de siège passager
- Housse d'appuie-tête



Glisser la housse sur le siège.



Aligner l'ouverture de l'appuie-tête et fixer la bande velcro.





Mettre la sangle en toile entre le haut et le bas du siège.



Tirer la sangle entre le siège, puis tirer sur la sangle.



Fixer la sangle en toile avec la boucle repassante.



Placer la housse sur le siège du bas.



Fixer le coussinet sur le côté de l'armature de siège.



Passer la sangle sous le siège et la fixer avec la boucle.



Demeurer à l'écart de tout connecteur électrique sous le siège.



Fixer la bande velcro pour immobiliser le rabat extérieur.

 *Maintenir le rabat derrière la fixation de ceinture de sécurité.*

Appuie-tête



Glisser la housse sur l'appuie-tête.

Appuie-tête



Fixer la bande velcro.

Asientos ergonómicos delanteros

**Asientos ergonómicos delanteros
CONTENIDO DEL ESTUCHE:**

- Cubierta de asiento del conductor
- Cubierta de asiento del pasajero
- Cubierta de cabecera



Deslice la cubierta sobre el asiento.



**Alinee la abertura de la cabecera
y conecte el velcro**





5

Coloque la correa tejida entre la parte superior e inferior del asiento



6



7

Jale el tejido entre el asiento y jale la correa tejida



8



9



10

Conecte la correa tejida con bloqueo de escalera

ALL INFORMATION WITHIN ABOVE BORDER TO BE PRINTED EXACTLY AS SHOWN ON 8.5 x 11 WHITE 16 POUND NON-BOND RECYCLABLE PAPER. PRINT ON BOTH SIDES, EXCLUDING TEMPLATES. TO BE UNUNITIZED IN ACCORDANCE WITH GM SPECIFICATIONS.	DATE	REVISION	AUTH	DR	TITLE INSTALLATION INSTRUCTIONS Carhartt Front Seat Covers
	23JA18	Initial Release - Gino LeDonne	2596136		
					PART NO. 84138071 SHEET 12 OF 15



Coloque la cubierta sobre el asiento inferior



Sujete la almohada al lado del marco del asiento



Pase el tejido debajo del asiento y alcance el tejido para conectar con la hebilla

 Mantenga alejado cualquier conector eléctrico debajo del asiento



Conecte el velcro para asegurar la aleta exterior

 Mantenga la aleta enrutada detrás de la conexión del cinturón de seguridad

Cabecera



Deslice la cubierta sobre la cabecera

DATE	REVISION	AUTH	DR
23JA18	Initial Release - Gino LeDonne	2596136	

INSTALLATION INSTRUCTIONS			
Carhartt Front Seat Covers			
PART NO.	84138071	SHEET	14 OF 15

Cabecera



Conecte el velcro